

JANE

Desks



JN2L-C3060L-OSFSD3-42

30"D 60"W X 42"H

JANE



JANE DESK

- Laminate tops have rigid 3mm PVC edges.
- Cabinet available in high-pressure laminate or thermally fused laminate.
- Laminate modesty panel.
- Rigid steel support frame.
- 60mm twin locking casters.
- Locking storage.
- Wire management grommet.
- Cabinet available with drawers or cupboard storage.

JANE DESK STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
JN2_-C3060_-29	30	60	29
JN2_-C3060_-C2_-29	30	60	29
JN2_-C3060_-OSFSD3-36	30	60	36
JN2_-C3060_-OSCS_-36	30	60	36
JN2_-C3060_-OSFSD3-42	30	60	42
JN2_-C3060_-OSCS_-42	30	60	42

CABINET CONFIGURATIONS:

(No designation) - 3 Drawers B/B/F

CSL/CSR - (29"H only) Cupboard Storage, Left hand hinge/right hand hinge

OSFSD3 - Open Storage, 3 Drawers (B/B/F on 36"H, B/F/F on 42"H

OSCSL/OSCSR - (36"H and 42"H) Open Storage, Cupboard Storage

Pictured above: JN2L-C3060L-OSFSD3-42 shown with HAN009 Hannah Task Stool



JN2L-C3060L-29



JN2R-C3060L-29

To Order, Choose Finish Selections & Options

Top: Choose from our high-pressure laminate options.

Cabinet: Choose from our high-pressure laminate or melamine options.

Edges: Choose from our PVC Choices.

Finish: Frame and legs require powder coat finish choice.

See **mediatechnologies'** Finish and Color Guide for choices at www.mediatechnologies.com.

General Specifications

Cabinet: Cabinet is constructed with 3/4" thick engineered wood with either thermally fused laminate or high pressure laminate box finish, 14-gauge perforated powder coated steel front panel and 3mm PVC edgebanding. Cabinet receives box and file drawers with full extension 100# ball bearing drawer slide and loop pulls or cupboard with one base and one adjustable shelf and right- or left-hand hinged door* with loop pull. 36"H and 42"H models receive open storage space.

Cabinet Frame: Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile cabinet unit uses (4) casters that attach via threaded inserts on underside of the steel frame assembly.

Desk Table Top: Bullet-shaped top is 1" thick, three-ply particleboard with .050" high-pressure laminate top surface and .030" phenolic backer. Edges are 3mm PVC (C). Corners on rectilinear end are square with a 1/8" radius. (2) Oval grommets are provided. One located in the worksurface and one located in the cabinet wall beneath the desk worksurface. Tables are fitted with a matching laminate modesty panel.

Desk Assembly: Desk can be provided with the cabinet positioned on the left (model number prefix JN2L) or on the right (model number prefix JN2R) of the user position.

Desk Leg Assembly: On 29"H models, leg set is 1-1/4", 14-gauge powder coated steel tubing. A steel brace is welded between the two legs for added stability. The legs are welded to a 3/16" thick steel top plate. The bottom of each leg is capped with a 1/4" plate and bored and tapped to allow the attachment of a 60mm caster with brake. On 36"H and 42"H models, cast aluminum base has one 2-1/4" diameter column with bolted horizontal cast aluminum base and fabricated steel mounting plate .187" thick x 6"D x 8"W. Bases are fitted with twin wheel locking casters.



cs-jane-191230

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

PURE MICHIGAN™