CONCIERGE

Tech Carts & Lecterns



CONCIERGE



Front View



Rear View

CONCIÉRGE EXPANDABLE SURFACE TECHNOLOGY CART

- Mobile Podiums feature a high pressure laminate work surface.
- Expandable work areas.
- · Wire management grommet is standard.
- · Decorative vented steel locking back.
- Fully adjustable concealed hinges and locking mechanism
- · Available in thermally fused laminate, high pressure laminate or veneer.
- · Rigid steel inner support frame prevents racking
- Casters mount to 1-1/4" x 1-1/4" steel frames.
- Customize with your organization's logo.
- · Cabinet locks are standard.

To Order, Choose Finish Selections & Options

Work Surface: Choose from our selection of high pressure laminates.

Edges: Choose your PVC edgeband color.

Cabinet: Choose your high pressure laminate, thermally fused laminate or wood veneer.

Steel Panel and Frame: Choose from our selection of powder coats.

See **mediatechnologies**' Finish and Color Guide for choices at www.mediatechnologies.com.

C C Squared Corners PULL OUT C C Squared Corners C C Squared Corners Fight or Left Side Pullout CASTERS Twin Wheel Locking

CONCIÉRGE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
PC_D-3242-MB	28	32	42



CUSTOMIZATION OPTION
We can customize your cart or podium
with your logo executed in a perforated
pattern or with a durable vinyl appliqué.
Contact us for details.

General Specifications

Table Top: Tops are 11/4" thick, three ply 45# particle board construction with .050" high pressure laminate top surface and a .030" phenolic backer. Edge is 3mm PVC with a 1/8" radius top and bottom.

Case Construction: Main cabinet modules are constructed of 3/4" thick three ply thermofused particleboard with TFL or premium wood veneer face or 3/4" thick vertical grade high pressure laminate. Modules utilize a full 3/4" particle board sub-top with finished 3mm wood edge. Cabinets are assembled using glue and dowel joinery. Cabinet assembly includes a ridged steel stabilizing frame constructed of 1" square 12 gauge steel with welded corner gussets. Frame is bolted to the interior of the cabinet. Mobile units use casters that attach via threaded inserts on underside of the steel frame assembly.

Steel Access Door: Rear accessing door is constructed of formed 14 gauge powder coated steel that is perforated for air flow. Door has a welding 1" x 2" rectangular tube welded on the height of the door to receive concealed European style hinges that are also mounted to cabinet case.

Adjustable Shelves: Adjustable shelves are constructed of 3/4" thick three ply thermofused particleboard OR 3/4" thick vertical grade high pressure laminate. Shelves attach with plastic AWI approved shelf clips.

Side Pull Out Shelf: Constructed of 3/4" thick three ply thermofused particleboard OR 3/4" thick vertical grade high pressure laminate, the shelf is mounted to the cabinet with ball bearing drawer slides and includes a laminate retainer. Shelf mounts in cabinet and through a routed opening in the left hand side of the cart (right hand slide is available also).



cs-concierge-190308

892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 F: 231.861.6678 www.mediatechnologies.com sales@mediatechnologies.com

