



Connect 2022



In Surface • Flush Mount

Powerspot



APSP-1P1UC-72-B

Standard Features:

- In surface, round, flush-mount power unit. Versatile. Compact, low profile design allows you to mount the unit in more places than ever before. Fast Device charging
- Receptacle configuration options:
 - 1 Power / 1 USB / 1 USB-C
- Fast Device Charging. All models provide two USB charging ports (5V, 3.1A total) one USB Type A and one USB Type C, ensuring that all of your devices charge as quickly as possible
- Versatile. Compact, low profile design allows you to mount the unit in more places than ever before
- UL Spill Water Compliant. Passed UL 962A spill water test requirements so it can even be used in a horizontal surface such as a table top
- Hole cut out dimensions: 2.5" diameter
- 72" and 120" cords available



Configurations:



-1P1UC

Colors:



White Black Nickel

2

Port



APRT-2P-120-W

Standard Features:

- Clean and simple flush mount design that compliments a wide range of aesthetics
- For mounting in hard surface
- Bezel and receptacle housing: molded plastic
- Receptacle configuration options:
 - 2 Power
 - 1 Power / 1 USB / 1 USB-C
- USB charging ports 2 amps each
- UL and CUL listed
- AC receptacles with Spill-Proof Technology
- 72" and 120" cords available (we suggest 120" for most applications)

Configurations:



-2P -1P2U -1P1UC

Colors:



White Black



Ensemble



AEMB-2P1UC-72-B

Standard Features:

- Versatile. Compact, low profile design
- Receptacle configuration options:
2 Power / 2 USB
2 Power / 1 USB / 1 USB-C
- Models have tamper-resistant receptacles to keep little fingers away from danger
- Fast Device Charging. Two USB charging ports (5V, 3.1A total) ensuring that all of your devices charge as quickly as possible
- UL Spill Water Compliant. Passed UL 962A spill water test requirements so it can even be used in a horizontal surface such as a table top
- Available in three attractive finishes: black, white and nickel, so you can match or complement any furniture style. Included bezel hides the mounting screws for a cleaner look
- Pass-thru plug allows you to connect the power center to any outlet, even one that is already being used
- 72" and 120" cords available



Configurations:



Colors:



Aztech



AZ-2P2U1O-120-B


Standard Features:

- For mounting in hard or upholstered surfaces
- Receptacle configuration options:
2 Power / 1 Dual USB / 1 Open Port*
- AC receptacles with Spill-Proof Technology
- 1 Dual USB charging port, 2 amps each port
- UL and CUL listed
- Vertical or horizontal mounting
- O.D. 8.125" x 3" (fits 6.625 x 1.875" cutout)
- Cutout for upholstered application may vary
- 72" and 120" 15 amp cords available

Configuration:



Colors:



*Open Port configuration includes a voice/data port adapter kit. See page 13.



2 Aztechs mounted in a Downtown table top.

In/On Surface • Monument

Jolt



AJLT-4P-72-W

Standard Features:

- Receptacle housing: high gloss plastic finish
- Receptacle configuration options:
 - 4 Power
 - 2 Power / 2 Dual USB
- UL and CUL listed
- Available with 2 amp dual USB
- AC receptacles feature Spill-Proof Technology
- Hole cut out dimensions: 3" diameter
- Fixture depth suitable for table tops 0.75"-1.5" thick
- 72" and 120" cords available

Configurations:



Colors:



Note: The -4P models require a plug with an integrated transformer that will not pass through table legs!

Duet



ADUF-1P2U-120-S


Standard Features:

- For use in upholstered surface applications
- Receptacle configuration options:
 - 2 Power
 - 1 Power / 1 Dual USB (2 amps each)
- AC receptacles with Spill-Proof Technology
- 1 Dual USB charging port, 2 amps each port
- UL listed
- Face Mount

Configuration:



Colors:



TREO



TRO-2P1UC-72-ST

Standard Features:

- Finish: smooth plastic faceplate with clear anodized aluminum housing, and powder-coated steel trim
- Receptacle configuration options:
 - 2 Power / 1 USB / 1 USB-C
- Available with Tamper Resistant Simplexes
- 15 Amp power simplexes
- Dual Port 4 Amp USB (2 Amps per port)
- UL Listed
- Fits 1.94" x 6.25" cut out
- 72" and 120" cords available

Configurations:



Colors:



Backstop



ABTP-2P2U-72-W



Standard Features:

- Offers sleek and easy-to-install solutions that mount directly on surfaces and minimize cord clutter
- Receptacle configuration options:
2 Power / 2 USB
3 Power / 2 USB
- Smart charging capability that recognizes devices and when to shut off during peak loads
- Easy connection to power sources. 72" (1.83m) 14 gauge pass-through cord easily reaches walls and floors
- Supports tables from 0.5" to 1.5" for the clamp mount. Under table bracket mount supports 1" to 1.5"
- Included Mounting Kit includes several mounting options for use under and above table surfaces for any environment
- 72" cords available

Configurations:

Colors:



Standley



STND-2P1UC/4P-72-B

Standard Features:

- Compatible with all standard sit/stand desk height ranges
- Includes one plug-in outlet center, one Desktop Power Center Slim and one 6' coiled cord
- Receptacle configuration options:
2 Power / 1 USB / 1 USB-C (above surface) +
4 Power (below surface)
- Options for horizontal and vertical applications
- UL 962A Spill Water Compliant and can be used in a horizontal surface such as a tabletop


Configuration:

Colors:

-2P1UC/4P



Grover



AGRV-2P2UC-B-96

Standard Features:

- Free-standing connectivity tower for convenient access to power and charging of devices.
- Receptacle Configuration:
2 Power / 2 USB-A / 2 USB-C
- 3' tall power tower designed to accommodate seated areas for convenient power access.
- Tamper-resistant receptacles to prevent users from injury.
- Available in black and white.
- Overall dimensions: 9.2"D x 9.2"W x 35.75"H
- Complies with FCC Part 15, Subpart B.
- 8' self-retracting power cord.

Configuration:

Colors:



In/On Surface • Flip Up Dual Up



AMX-4P8U-72-SAWT

*Open Port configuration includes a voice/data port adapter kit. See page 13.

Standard Features:

- Dual flip up
- Bezel and receptacle housing: anodized aluminum
- Receptacle configuration options:
 - 4 Power / 4 USB / 2 Open Ports*
 - 4 Power / 4 USB / 2 USB-C
- UL listed
- AC receptacles with Spill-Proof Technology
- USB charging ports 2 amps each
- Fits 7.8125" x 7.5455" cutout
- 72" and 120" 15 amp cords available

Configurations:



-4P4U2O

-4P4U2C

-4P8U

Colors:



-SAWT
Silver
Powder Coat/
White Trim

Envoy



AENV-2P2U-72-B

Standard Features:

- Unobtrusive with maximum accessibility and flexibility
- Receptacle configuration options:
 - 2 Power / 2 USB
- Soft Opening Cover Mechanism – opening and closing the cover is quieter and easier with a more professional feel. Opens slowly & quietly, without “snapping open”
- Allows access to services on, above or below the work surface with cord ended or field-wired options
- Tamper-resistant receptacles
- Variety of applications include: office workstations, conference rooms, even home offices can increase productivity by bringing access to connections up to the work surface
- USB Charging Capability: Duplex 3.1A USB receptacles provide charging capacity for a wide range of mobile devices
- 72" cord available

Configurations:



-2P2U

Colors:



-B
Black



-SS
Stainless
Steel

Sparky



SPK-1P1U1WCS-72-B

Standard Features:

- Offers wide-ranging functionality with clean, modern design for a powerful all-in-one solution
- Receptacle configuration options:
 - 1 Power / 1 USB / 1 Wireless Charging Surface
- Compatible with all Qi enabled smart phones and devices
- 5 Watt Qi Charging Coils
- 15 Amp Power Simplex
- Single Port USB, 2 Amps
- 3" diameter cutout in work surface
- Gloss plastic with Qi charging inserts
- 72" and 120" 15 amp cords available

Configurations:



-1P1U1WCS

Colors:



-W
White



-B
Black

Charge Up



ACUS-3P1UC-72-W

*Open Port configuration includes a voice/data port adapter kit. See page 13.

Standard Features:

- Subtle and sophisticated single flip up
- Bezel and receptacle housing: High gloss molded plastic
- Receptacle configuration options:
3 Power / 1 USB-A / 1 USB-C
1 Open Port* / 3 Power
- UL listed
- AC receptacles with Spill-Proof Technology
- USB charging ports 2 amps each
- Fits 3" x 6.9375" cut out
- 72" and 120" 15 amp cords available

Configurations:



Colors:



Mini Charge Up



ACUM-2P-72-W

Standard Features:

- Keeps a low profile, but rises up when needed to reveal a dynamic range of power and data configurations.
- Single flip up
- Receptacle configuration options:
1 USB / 2 USB-C / 1 Power
2 Power
- UL listed
- AC receptacles with Spill-Proof Technology
- USB charging ports 2 amps each
- Fits 3.5" x 4.5" cut out
- 72" and 120" 15 amp cords available

Configurations:



Colors:



Track Star




TSTR-2P-72

Standard Features:

- Perfect for conference rooms, lecterns, desks and more
- Receptacle configuration options:
2 Power / 4 Data Ports
- Accommodates a single power/data point with a single circuit
- Always includes 2 power outlets, 4 data ports and low-profile transition ramps
- Clear Anodized finish
- Available in 6' and 12' lengths
- ADA compliant and tested to UL standards 962A in US and C22.2 #21 in Canada

Configurations:



Colors:



Power Strips • Plug In Outlet Centers

Heavy Duty Outlet Center



HDPS-6P


Standard Features:

- User ready outlets provide power distribution in a portable, plug-in unit
- Receptacle configuration options:
 - 6 Power
- Durable 2" x 1 3/4" [44mm x 51mm] or 3 1/2" x 2" [89mm x 44mm] aluminum housing. Some units are available with an impact resistant plastic housing
- Rack mount units fit standard 19" [482mm] relay racks
- Compact 1U design takes up minimum space
- Low profile. CabinetMATE units offer a narrow 1 1/2" x 1 3/16" [38mm x 20mm] aluminum housing

Configurations:



Colors:



Plastic Plug-In Outlet Center



PPOC-4P1UC

Standard Features:

- This Plug-In Outlet Center offers power outlets and USB ports in a slim profile, keeping laptops and electronics charged and ready for work
- Receptacle configuration options:
 - 4 Power / 1USB / 1USB-C
- User-ready: Power outlets and USB ports are housed in a portable, plug-in unit
- Available with USB-C PD & USB-A
- Total output of 20 Watts
- Surge protected LED indicator
- Easy-to-spot surge protection for users

Configurations:



Colors:



P6 Power Strip



P6PS-6P

Standard Features:

- Includes six outlets in a putty white impact-resistant housing
- Polymeric / 120 volts
- Receptacle configuration options:
 - 6 Power
- Delivers 15A of power with a lighted switch
- Includes 6ft 14/3 SJT white cord with NEMA 5-15 plug

Configurations:



Colors:



ModuLink

Standard Features:

- Create a system of power for workstations, training and flexible workspaces. Easily connect up to six power units together with our sleek, slim and unobtrusive modular, code compliant ModuLink.
- Receptacle configuration options:
3 Power / 1USB / 1USB-C
- Models include three 15A receptacles, one USB Type-A port and one USB Type-C port for 15W of shared power
- Easy installation for quick changes and moves
- Power and charging combinations that get the job done
- Models include three 15A receptacles, one USB Type-A port and one USB Type-C port for 15W of shared power
- Jumper Cable accessory to add length to any system
- Sleek, slim design fits unobtrusively on work surfaces
- Each unit includes cord clips for cable management to keep the space tidy
- Passed UL 962A spill water test requirements and can be installed in a horizontal surface such as a tabletop
- This device complies with FCC Part 15, Subpart B
- Fits 2.25" x 7.15" cut out
- Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation

Configurations:



Colors:



MDS-3P1UC




MDT-3P1UC
Termination Unit



MDE-3P1UC
Middle Unit



MDS-3P1UC
Starter Unit



Modular Systems

ModTrak 4




Shown mounted beneath table top

Standard Features:

- Mount below worksurface, in troughs, or in the panels of your cubicle jungle
- 4 wires, 1 or 2 circuits, 20 amps each (Circuit 1 and 2 only depending on power entry)
- 13 - Duplex receptacles per circuit
- 26 - 15 Amp duplex receptacles per power infeed maximum
- Easy to install and reconfigure
- Requires less space
- UL recognized as an office furnishing accessory
- UL Listed as Manufactured Wiring System
- More economical than 8-Wire System


36" Table Kit

Model Number: MT-4T-36




48" Table Kit

Model Number: MT-4T-48




60" Table Kit

Model Number: MT-4T-60



72" Table Kit

Model Number: MT-4T-72



Each kit includes (2) Duplexes, (2) Jumper-M's and (2) Mounting Brackets.

Jumper-M



JMM-18

Model Number: JMM-



- 9", 12", 18" 22", 24", 30", 36", 42", 48" available lengths

Jumper-F



JMF-18

Model Number: JMF-




- 9", 12", 18" 22", 24", 30", 36", 42", 48" available lengths

Single Circuit Power Entry



SCPE-72

Model Number: SCPE-72



- 20 AMP
- 72"
- Only permits one circuit per power entry

2-Circuit Power Entry



MT-4T-MLPE-72

Model Number: MT-4T-MLPE-72




- 2 Circuit Power Entry
- 72"
- Must be hard wired by an electrician

Mounting Bracket



MT-4C-MBK

Model Number: MT-4C-MBK



- Aluminum mounting bracket
- 2 hex head screws

Accessories

Grommets



A25GD-



A30GU



A20GU


Standard Features:

- Plastic wire grommet
- Adjustable hole openings for A30GU & A20GU
- 50mm & 80mm Round
- Purchase installed or un-installed
- Black finish (A25GD- is also offered in white)
- A25GD- is used for vertical conditions

Cable Grip



ACG-5B



Shown mounted
beneath table top

Standard Features:

- Plastic cable grips
- Available in black
- 2.5"W x 5.375"L

Vertical Cable Management



Standard Features:

- Vertical Wire Management
- Split cable loom with weighted metal
- Base and table attachments
- Easy to adjust by adding or removing plastic discs as required
- Available in silver or black
- 4"W x 4"D x 32"H

AVM32-VERTS

Cord Storage Basket



CSB24

Standard Features:

- Carbon steel basket tray
- Holds cords and cables with simple, open design
- Easy to install under desks or tables

Cable Channel



Standard Features:

- PVC Wire management channel
- 2.5"W x 1.5"H x 48"

AWM48

Rotating CPU Holder



ACPU-CS-11

Standard Features:

- Under-desk mounting kit
- Width adjusts from 5.25" to 9.25"
- Height adjusts from 15.375" to 21"
- Rotates 180 degrees

CPU Holder



Standard Features:

- Under-desk mounting kit
- Width adjusts from 5.25" to 9.25"
- Height adjusts from 15.375" to 21"

ACPU-CS-10

Articulating Keyboard Combo



AAK1003

Standard Features:

- Articulating keyboard mechanism
- Mouse tray clamps to mechanism
- Slide out, swivel and tilt, lock positions
- Includes padded wrist rest

Accessories

Bag Hook




BPH

Standard Features:

- For storage of bags underneath most tables and desks

*Open Port Voice/Data Adapter Kits



Voice/Data Adapter Tree

Voice/Data Adapter kits are included with all power access devices that are configured with Open Ports.

The Voice/Adapter kit allows jacks and couplers to be used in any power access device that is configured with Open Ports.

Choose the appropriate adapter, install your jack or coupler and snap it into place into the Open Port's modular window.

Adapter trees are delivered in black or white to match your device. Note: for configurable units only.

Warranty Information

Prices: All prices are F.O.B. the factory. Prices and specifications are subject to change without notice. Prices do not include applicable taxes, special handling or installation charges. Possession of a price list is not an offer to or agreement to sell. We reserve the right to change prices without notice. We are not responsible for typographical errors. In the event a price or description is found to be incorrect, the correct information will be communicated to you when the order is received.

Credit Terms: Open account status is only granted after a completed credit application is received and approved.

Payment Terms: Terms for open account are net 30 days. Terms for orders without open account will be determined by Mediatechnologies LLC on an order-by-order basis and may require prepayment or a 50% deposit with order and the balance prepaid before shipment.

Orders: Orders must be in writing. Faxed orders are acceptable. Processing of orders will not begin until a signed acknowledgment is received.

Acknowledgments: Orders are accepted, manufactured and invoiced based on written acknowledgments issued by Mediatechnologies LLC. All orders are considered correct as acknowledged. Notify Mediatechnologies LLC immediately of any order discrepancies. Acknowledged orders may not be changed or canceled without written consent from Mediatechnologies LLC.

Changes to orders: Changes to orders already in process may be subject to a fee covering the cost to make the requested change. If a fee is necessary a written authorization of acceptance will be required. All requests for changes are subject to approval by Mediatechnologies LLC.

Cancellation of orders: All orders received by Mediatechnologies LLC are considered firm and cannot be canceled without our approval. A cancellation fee may be required based upon cost incurred by Mediatechnologies LLC prior to receipt of a cancellation request.

Returns: Returns are not accepted without a Return Goods Authorization issued by Mediatechnologies LLC. Unauthorized returns will not be accepted. Returns may be subject to a restocking fee.

Shipping Terms: All orders will be shipped F.O.B. shipping point with freight charged collect. Shipping weights listed are net.

Routing: Shipments will be routed "best way" or as specified. Instructions will be followed as closely as possible, however, Mediatechnologies LLC reserves the right to make changes due to local conditions or other circumstances.

Freight Damage: Legal title to merchandise passes to the buyer upon acceptance by the carrier. All cartons must be carefully inspected at the time of delivery. Visible damage should be noted on the delivery receipt. In the case of concealed damage, the carrier must be notified within (5) days. It is the buyer's obligation to seek recourse against the shipper.

Shortages: Shipments should be inspected upon receipt for shortages. Shortages must be reported to Mediatechnologies LLC in writing within (5) days of receipt.

Shipping Address:

mediatechnologies®
892 Industrial Park Drive
Shelby, MI 49455

Warranty: All items manufactured by Mediatechnologies LLC, home of mediatechnologies® and elements by mediatechnologies are guaranteed against defects for a period of five (5) years from the date of purchase. We will repair or replace, in our discretion, any defective item without cost to our customer. This is the customer's sole and exclusive remedy against us. No delay in shipment or delivery shall give rise to any liability for damages whatsoever. We are not liable for defects caused by customer or any third party. Customer is not authorized to make any repairs whatsoever or to deduct any amount from the purchase price. In no event shall our liability under this warranty exceed the purchase price. In no event shall we be liable for incidental, special or consequential damages. We disclaim all other warranties, express or implied, as to any matter whatsoever, including without limitation, quality, design, performance, specifications, samples, condition, merchantability and fitness for any particular purpose. No action may be commenced for breach of the warranty more than six months after the cause of action accrues and any such action may only be brought in the county of Oceana, State of Michigan.



www.mediatechnologies.com

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

connect electrical 2301

PURE MICHIGAN®