

Occasional Tables

General Specifications

Table Top: Table tops are 1-1/4" thick, three-ply engineered wood construction, with .050" high-pressure laminate (HPL) surface and a phenolic backer. The standard edge is 3mm PVC. Tops 60" and over are supported on the underside with a 14 gauge steel keel.

Legs: The legs are 2-1/4" solid glued up red oak with a 3/8" radius on all long edges. They are attached to the top by means of a 5"x5/16" steel plate. The leg and the plate are joined by (2) 5/16-18 maching bolts screwed into a 1/2" diameter barrel nut which is embeddedin the leg. The steel plate is attached to the table top by (5) 5/16-18 machine bolts which screw into 5/16-18 metal insert embedded in the top. Each leg is equipped with a leveling guide.

Finish: Standard powder coat on all metal parts is black; other colors may be specified. See mediatechnologies® Finish and Color Guide for choices.





Vector Occasional Tables **Model Number** Wgt **List Price** Description VT-C2424-18 24"W x 24"D x 18"H 38 \$793 VT-C2424-22 24"W x 24"D x 22"H 38 \$793 VT-C3030-18 30"W x 30"D x 18"H 42 \$806 VT-C3030-22 30"W x 30"D x 22"H 42 \$806



VT-C2448-18 24"W x 48"D x 18"H VT-C2448-22 24"W x 48"D x 22"H



		R	ound Tables
VT-C0030-18	30" Diameter x 18"H	39	\$1,282
VT-C0030-22	30" Diameter x 22"H	39	\$1.282

60

60

\$1,002

\$1,002

Required to order: Model # including options if applicable

- HPL selection
- PVC selection
- powder coat selection