PLATFORM

Chairs & Stools



PL-19LC PLBS-31C PLS-31LC 19.75"D x 16"W x 19"SH 19.75"D x 16"W x 31"SH 19.75"D x 16"W x 31"SH



PLATFORM





Back Detail

PLATFORM

- Strong, clean lines and a striking combination of natural and industrial materials give this chair a functional yet futuristic beauty.
- Upholstered seat cushion is 3" high-density upholstery grade foam on a 3/4" engineered wood base with a TFL face. Seat is bolted to frame using metal-to-metal connection.
- Seat back is fabricated of 1" thick Baltic birch with your choice of laminate. Edges are exposed Baltic birch tapered and profiled with a radius along the corners.
- Powder coated frame.
- Stool is available with and without seat back.
- Frame of stool includes a welded steel foot rail.
- Legs are fitted with leveling glides.

PLATFORM CHAIR STANDARD SIZES

MODEL	DEPTH"	WIDTH"	SEAT HEIGHT"	
		OVERALL HEIGHT 37.5"		
PL-19_	19.75	16	19	

PLATFORM STOOL STANDARD SIZES

MODEL	DEPTH"	WIDTH"	SEAT HEIGHT"
		OVERALL HEIGHT 31" (BACKLESS)	
PLBS-31_	19.75	16	31
		OVE	RALL HEIGHT 43.5"
PLS-31_	19.75	16	31

To Order, Choose Finish Selections & Options

Seat Back: Choose from our selection of high-pressure laminates.

Seat Cushion: Choose a fabric for seat cushion.

Steel legs: Select a powder coat finish.

See mediatechnologies' Finish selections at https://www.mediatechnologies.com/resources/finishes View our fabric choices at https://www.mediatechnologies.com/resources/fabrics

General Specifications

Upholstered Seat: Seat cushions are 3" high-density upholstery grade foam on a 3/4" engineered wood base with a TFL face. Seat is bolted to frame using metal-to-metal connection.

Seat Back: Seat back is fabricated of 1" thick Baltic birch with laminate faces. Seat back edges are exposed Baltic birch tapered and profiled with a radius along the corners. Seat backs are bolted to a flat metal mounting "L" bracket. The "L" bracket is bolted to the bottom of the seat cushion and chair frame using metal-to-metal connection.

 $\label{eq:Frame:The frame} \textbf{Frame:} The frame assembly is comprised of 1.25" square 14-gauge powder coated steel tubing. The 15.75"D x 15.75"W x 28.75"H frame (including levelers) is completely welded. Frame includes a welded steel foot rail.$



cs-platform-180820



