RUBIX 36"W Storage





CCB3672-24-MB-T OS3636-24-MB-T 24"D x 36"W x 72"H 24"D x 36"W x 36"H



RUBIX 36"W





Cupboard Cubicle Storage

CCB3636-18-MB-TT

Cupboard Storage CS3629-24-MB-TT



Drawer Storage

DS3636-18-MB-TT

Open Cubicle Storage Adjustable OCB6-3636-18-MB-T





Open Cubicle

Wardrobe Storage WRS3672-24-MB-TT

36" WIDE RUBIX STORAGE UNITS

• High pressure laminate worksurfaces.

Open Tote Rail Storage

TOTOS3636-24-MB-T

with Open Storage

- Powder coated steel frame.
- Open Storage cabinets come with adjustable shelves.
- Optional 3" legs available upon request.
- Mobile units come equipped with 75mm casters.
- Not all configurations are available in every dimension combination.
- Totes for TOTOS & CSTOT models (TOT03-_ & TOT06-_)
 sold separately.

RUBIX 36"W STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
OPEN STORAGE (OS)			
OS3618-MB-T	18	36	29, 36, 42, 54
OS3624-MB-T	24	36	29, 36, 42, 54,72
CUPBOARD STORAGE (CS)			
CS3618-MB-TT	18	36	29, 36, 42, 54
CS3624-MB-TT	24	36	29, 36, 42, 54, 72
OPEN CUBICLE STORAGE (OCB) ADJ. SHELVES			
OCB4-3618-MB-T	18	36	29, 36, 42
OCB4-3624-MB-T	24	36	29, 36, 42, 72
OPEN CUBICLE STORAGE (OCB) FIXED SHELVES			
OCB12-36MB-T			
OPEN TOTE RAIL STORAGE WITH OPEN STORAGE (TOTOS)			
TOTOS3624-MB-T	24	36	29,36, 42
CUPBOARD CUBICLE STORAGE (CCB)			
CCB3618-MB-TT	18	36	29,36, 42
CCB3624-MB-TT	24	36	29, 36, 42, 72
	DRAWER STORAGE (DS)		
DS36MB-TT	18, 24	36	36, 42
CUPBOARD WITH TOTE RAIL STORAGE (CSTOT)			
CSTOT3672-24-MB-TT	24	36	72
WARDROBE STORAGE (WRS)			
WRS3672-24-MB-TT	24	36	72



892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 F: 231.861.6678 www.mediatechnologies.com sales@mediatechnologies.com

To Order, Choose Finish Selections & Options

Work Surface (if applicable): Choose from our selection of high pressure laminates.


Cabinet: Select HPL, melamine or veneer finish.

Edge: Choose from our selection of PVC or wood edges.

Steel Frame: Choose from our selection of powder coats.

Pull: Choose from our selection of Pulls.

See mediatechnologies' Finish and Color Guide for choices at https://www.mediatechnologies.com/resources/finishes



General Specifications

Cabinet: Are constructed with 3/4" thick engineered wood sides panels, sub-tops, vertical dividers and shelves. Backs are constructed with 3/4" thick engineered wood. Cabinet finish material includes high-pressure laminate and melamine with PVC edges and wood veneer with wood edges. Worksurface tops receive a high-pressure laminate surface. Cabinets 72"H or taller do not receive a worksurface top

Frame: Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile units use 75mm twin wheel locking casters that attach via threaded inserts on underside of the steel frame assembly. Freestanding steel support legs and mobile casters use the same threaded inserts and are interchangeable. Legs are available upon request.

Features of various cabinet configurations includes:

- Concealed door hinges and a variety of pulls available
 Full-extension drawers
- TOTR Tote rails for use of both TOT03-_ and TOT06-_ Toto totes.

Rubix36_CS_210505



