

General Specifications


Cabinet: Open storage cabinet with divider is constructed with 3/4" thick engineered wood with either thermally fused laminate or high pressure laminate box finish and 3mm PVC edging. Structural back panel is 18 ga. Steel with 1/4" square perforations in a decorative pattern for ventilation. The cabinet is bolted to the leg frame assembly with threaded fasteners using a metal-to-metal connection.

Tops: Tops are 1.25" thick, three-ply particleboard with .050" high-pressure laminate top surface and .030" phenolic backer. Edges are 3mm PVC (C). Radiused corners on lower work surface. Corners on upper surface are square with a 1/8"radius. Upper work surface is fitted on the user end with a 1/8" metal retainer edge.

Leg Frame Assembly: Each leg end set is 1-1/4", 14-gauge powder coated steel tubing formed into a "U" shape. A steel brace is welded between the two legs for added stability. The two leg end sets are welded together with two 1-1/4", 14-gauge powder coated square steel tubing stringers. The bottom of each leg is capped with a 1/4" plate and bored and tapped to allow the attachment of a 60mm caster with brake.

Finish: Standard powder coat on all metal parts is black; other colors may be specified. See mediatechnologies® Finish and Color Guide for choices.





Richard Podium			
Model Number	Description	Wgt	List Price
TFL Panels with 3mm PVC Edges			
RC-2330T-42-4C	Podium, 23" x 30" x 42"H, Mobile		\$2,470
HPL Panels with 3mm PVC Edges			
RC-2330L-42-4C	Podium, 23" x 30" x 42"H, Mobile		\$2,806

- Required to order:** Model # including options if applicable
- HPL selection
 - PVC selection or wood edge finish
 - melamine selection (if applicable)
 - powder coat selection