

GTX CARREL

Tables



GTXSCT-C3036-29

30"D X 36"W X 29"H, 40"OAH

GTX CARREL



GTXSCT-C3036-29



GTXDCT-C6072-29

GTX Carrel Table

- 14-gauge steel leg frames bolt into a double steel keel assembly for a rigid base.
- 1-1/4" thick work surface "floats" on 3/4" spacers bolted through the steel frame assembly into the underside of the work surface.
- High-pressure laminate work surface and privacy panels.
- Single-faced and double-faced carrels available
- 1 wire management grommet per station is standard
- Legs fitted with adjustable leveling glides.

To Order, Choose Finish Selections & Options

Work Surface: Choose from our selection of high-pressure laminates.

Edges: Choose PVC edgeband.

Frame: Choose powder coat option for steel frame.


See **mediatechnologies'** Finish and Color Guide for options at www.mediatechnologies.com.

GTX CARREL TABLES - SINGLE FACED

MODEL	DEPTH"	WIDTH"	HEIGHT"
OVERALL CARREL HEIGHT IS 40"			
GTXSCT-C2436-29	24	36	29
GTXSCT-C2460-29	24	60	29
GTXSCT-C2472-29	24	72	29
GTXSCT-C3036-29	30	36	29
GTXSCT-C3060-29	30	60	29
GTXSCT-C3072-29	30	72	29
WORK SURFACE HEIGHT IS 29"			

GTX CARREL TABLES - DOUBLE FACED

MODEL	DEPTH"	WIDTH"	HEIGHT"
OVERALL CARREL HEIGHT IS 40"			
GTXDCT-C4836-29	48	36	29
GTXDCT-C4860-29	48	60	29
GTXDCT-C4872-29	48	72	29
GTXDCT-C6036-29	60	36	29
GTXDCT-C6060-29	60	60	29
GTXDCT-C6072-29	60	72	29
WORK SURFACE HEIGHT IS 29"			
DOUBLE-FACE CARRELS ARE FACE-TO-FACE SEP. BY A PRIVACY WALL			



General Specifications

Table tops: 1-1/4" thick, three-ply 45# particleboard construction with a .050" high pressure laminate top surface and a .030" phenolic backer and 3mm PVC edgeband.

Corners for rectilinear tops: square corners on banded tops have a 1/8" radius.

Privacy panels: 1" thick, three-ply 45# particleboard construction with a .050" high pressure laminate surfaces and 3mm PVC edgeband.

Leg and Frame Assembly: Welded end frames consist of 1-1/2" square, 14 gauge steel tubing. End frames are connected to (2) 1-1/2" square steel tube spanners using 1/4-20 machine bolts. 3/4" diameter x 3/4"H spacers are placed between the top and the understructure. Frame assembly attaches to work surface using 1/4-20 machine bolts. Legs are fitted with adjustable glides.



gtxcarrel-cs-200402

892 Industrial Park Drive
 Shelby, MI 49455
 P: 231.861.2194
 F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

