# FULL TIME OTTABLES

### **Occasional Tables**



FTDT-36-5C 36"DIA X 18"H



## FULL TIME OTTABLES





Round



FTST-3636 Square

FTRT-2436 Rectangle

FULL TIME OTTABLES

- Upholstered 1" thick assembled wood frame is topped with a 1" thick high pressure laminate work surface.
- Work surface is 18" high with 3mm PVC edges.
- Fitted with ABS self-leveling glides.
- · Casters are optional.
- Mates well with Full Time Ottomans!

#### **ROUND STANDARD SIZES**

MODEL	DIA.	HEIGHT"
FTDT-20	20	18
FTDT-36	36	18
FTDT-51	51	18

#### **CURVE STANDARD SIZES**

MODEL	CURVE	RETURNS	HEIGHT
FTCT-60	60°	24	18

#### **SQUARE STANDARD SIZES**

MODEL	WIDTH"	HEIGHT"
FTST-2424	24	18
FTST-3636	36	18

#### RECTANGLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
FTRT-1836	18	36	18
FTRT-2436	24	36	18
FTRT-2448	24	48	18

#### To Order, Choose Finish Selections & Options

**Upholstery:** Choose upholstery

Work surface: Choose high pressure laminate and PVC edgeband.

Steel Legs: Choose Powder Coat

See mediatechnologies' View our finishe choices at: https://www.mediatechnologies.com/resources/finishes View Fabrics at:

https://www.mediatechnologies.com/resources/fabrics



CONNECTIVITY

See our Connect Brochure.

Connectivity available in workurface only.

#### General Specifications

**Work surface:** Work surfaces are 1" thick, with a 7/8" particleboard core, .050" high-pressure laminate top and a .030 or thicker phenolic backer. Edge is 1/8 PVC. Work surface shapes match the base shapes and are available in round, square, rectangle and 30°curve shapes.

**Leg Assemblies:** Each leg is a weldment fabricated from 5/16" plate steel with a square mounting plate and curved vertical member. The bottom of each leg is fitted with a threaded weld nut and 1-7/8" black leveling glide. Powder coat finish. Four 75mm diameter casters can be substituted for legs at no charge. (FTD-20 uses (5) 50mm diameter casters.)



cs-fulltime\_ottables-190130



