

Charleston Carrel Tables

Tables

General Specification



Table Top: Tops are 1-1/4" thick, three ply engineered wood construction with .050" high pressure laminate (HPL) and a phenolic backer sheet. The Charleston edge is 5/8" x 1-1/4" solid red oak with the vertical face gently rounded to a 1-1/4" radius. Corners on rectangular and square tables are clipped at 45° and banded with 1/8" solid oak. Tops 60" and over are supported on the underside with 14 gauge steel keel.

Legs: The legs are 2" x 3" tapering to 2" x 2" at the bottom and set 45° to the aprons. Table legs are capped at the bottom with a finished steel boot. The top of each leg is machined to accept aprons from two sides and is bored and fitted with two threaded metal inserts for mounting bolts. Each leg is equipped with a levelling glide. Edges receive a hard sand break.

Apron: The apron is 1" x 3" with a hard sand break on exposed edges. Aprons receive a 12 gauge steel bracket on each end and form a structural frame that supports the top. Mounting bolts pass through the brackets at each corner of the frame into the legs and, when tightened, rigidify the entire assembly. Table top is screwed to the apron frame through pocket holes machined in the inside faces of the aprons.

Specify: model number/edge/wood finish/laminate/height
(Pricing shown is for oak)

All tables meet BIFMA standards.

Carrel Tables	Model Number	Description	Wgt.	Price
	CL2436CT	Charleston Carrel Table, 24"D X 36"W	71	\$1,691.00
	CL3036CT	Charleston Carrel Table, 30"D X 36"W	81	\$1,846.00
	CL2472CT	Charleston Carrel Table, 24"D X 72"W	121	\$2,222.00
	CL3072CT	Charleston Carrel Table, 30"D X 72"W	140	\$2,207.00