## **Privacy**

## **General Specifications**


**Table tops:** 1-1/4" thick, three-ply 45# particleboard construction with a .050" high pressure laminate top surface and a .030" phenolic backer. 3mm PVC edgeband.

Corners for rectilinear tops: square corners on banded tops have a 1/8" radius. Typical worksurface height is 29". Overall carrel height is 40"

Privacy panels: 1" thick, three-ply 45# particleboard construction with a .050" high pressure laminate surfaces. 3mm PVC edgeband.

Leg and Frame Assembly: Welded end frames consist of 1-1/2" square, 14 gauge steel tubing. End frames are connected to (2) 1-1/2" square steel tube spanners using 1/4-20 machine bolts. 3/4" diameter X 3/4"H spacers are placed between the top and the understructure. Frame assembly attaches to worksurface using 1/4-20 machine bolts. Legs are fitted with adjustable glides.

Finish: See mediatechnologies® Finish and Color Guide for choices.




		Double-Faced	
Model Number	Top Dimensions	Wgt	List Price
GTXDCT-C4836-29	48"D X 36"W	133	\$1,958
GTXDCT-C4860-29	48"D X 60"W	173	\$2,280
GTXDCT-C4872-29	48"D X 72"W	197	\$2,507
GTXDCT-C6036-29	60"D X 36"W	153	\$2,177
GTXDCT-C6060-29	60"D X 60"W	199	\$2,442
GTXDCT-C6072-29	60"D X 72"W	227	\$2,682

Carrels are face-to-face with a

privacy panel between		
Set Up Charges and Upcharges for Non-Standard and Custom Finishes		
Model Number	Description	List Price
Group 2 Powder Coat	Set up charge, per color, per order, for Group 2 Powder Coat	\$312
Non-Standard PVC	Upcharge, per color, per order, for non-standard PVC	\$865

- Typical worksurface height is 29"
- . Typical carrel height is 40"
- One wire management grommet per user location is standard



Required to order: Model # including options if applicable

- HPL selection
- PVC selection
- powder coat selection