# GTX COMMUNITY

# **Tables**





# **GTX COMMUNITY**





### GTX COMMUNITY TABLE

- 4 sets of 14-gauge powder coated steel leg frames bolt into a double steel keel assembly for a rigid base.
- 1-1/4" thick top "floats" on 3/4" spacers bolted through the steel frame assembly into the underside of the work surface.
- High-pressure laminate work surface.
- · Legs fitted with adjustable leveling glides.
- Optional casters available.
- Edges are 3mm PVC.

#### EDGE TYPES CORNERS С Squared 8mm Corners 3mm PVC Wood E\*\* J 3mm 3mm Wood Wood CASTERS 1-1/2" Flip Wood \*\*Square and rectangle tops only.

# **GTX COMMUNITY STANDARD SIZES**

| MODEL      | DEPTH" | WIDTH" | HEIGHT" |
|------------|--------|--------|---------|
| GTXC4296-  | 42     | 96     | 36/42   |
| GTXC42120- | 42     | 120    | 36/42   |
| GTXC4896-  | 48     | 96     | 36/42   |
| GTXC48120- | 48     | 120    | 36/42   |

# To Order, Choose Finish Selections & Options

**Work surface:** Choose your high pressure laminate and PVC edge band or wood veneer and wood edges.

Frame: Choose from our powder coat selection.

See **mediatechnologies**' Finish and Color Guide for choices. View our finish choices at www.mediatechnologies.com.

## POWER/CONNECTIVITY

- 2 power/2 active USB
- 1 open port
- 72" long cord
- Black or white finish



### General Specifications

**Table tops:** 1-1/4" thick, three-ply 45# particleboard construction with a .050" high-pressure laminate top surface and a .030" phenolic backer.

Corners for rectilinear tops: Square corners on banded tops have a 1/8" radius. Top floats on 3/4" spacers bolted through the steel frame assembly into the underside of the work surface.

**Leg and Frame Assembly:** 4 sets of 14-gauge powder coated steel leg frames bolt into a double steel keel assembly. Welded end frames consist of 1-1/2" square, 14 gauge steel tubing. End frames are connected to (2) 1-1/2" square steel tube spanners using 1/4-20 machine bolts. 3/4" diameter  $\times 3/4$ "H spacers are placed between the top and the understructure. Frame assembly attaches to work surface using 1/4-20 machine bolts. Legs are fitted with adjustable leveling glides. Twin wheel locking casters are optional.



cs-gtxcommunitytable-1800711



