

RUBIX 60"W

Storage



CSDFSL6029-24

24"D x 60"W x 29"H

RUBIX 60"W



Cupboard storage with (2) Lateral File Drawers (CS2FSL)
CS2FSL6036-24



Cupboard with (1) Deep Box Drawer & (1) Lateral File Drawer (CSDFSL)
CSDFSL6029-24



Cupboard Storage (CS)
CS6029-24



Cupboard with Open Storage (CSOS)
CSOS6029-24



Open Storage (OS)
OS6029-24



Open Storage Alternate Shelves (OSA)
OSA6029-24

60" WIDE RUBIX STORAGE UNITS

- High pressure laminate work surfaces.
- Powder coated steel frame.
- Open Storage cabinets come with adjustable shelves.
- Mobile units come equipped with 75mm casters.
- Optional 3" legs available upon request.
- Not all configurations are available in every dimension combination.

PULLS



RUBIX 60"W STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
CUPBOARD STORAGE (CS)			
CS60_ _	18, 24	60	29, 36
CUPBOARD WITH OPEN STORAGE (CSOS)			
CSOS60_ _	18, 24	60	29, 36
OPEN STORAGE (OS)			
OS60_ _	18, 24	60	29, 36
OPEN STORAGE ALTERNATE SHELVES (OSA)			
OSA60_ _	18, 24	60	29, 36
CUPBOARD WITH BOX & LATERAL FILE DRAWER (CSDFSL)			
CSDFSL6029_ _	18, 24	60	29
CUPBOARD WITH LATERAL FILE DRAWERS (CS2FSL)			
CS2FSL6036_ _	18, 24	60	36

To Order, Choose Finish Selections & Options

Work Surface (if applicable): Choose from our selection of high pressure laminates.

Cabinet: Select HPL, melamine or veneer finish.

Edge: Choose from our selection of PVC or wood edges.

Steel Frame: Choose from our selection of powder coats.

Pull: Choose from our selection of Pulls.

See **mediatechnologies'** finish selections at <https://www.mediatechnologies.com/resources/finishes>

CORNERS



CASTERS



General Specifications

Cabinet: Cabinets are constructed with 3/4" thick engineered wood side panels, sub-tops, vertical dividers and shelves. Backs are constructed with 3/4" thick engineered wood. Cabinet finish material includes high pressure laminate and melamine with PVC edges and wood veneer with wood edges. Work surface tops receive a high pressure laminate surface. Cabinets 72"H or taller do not receive a work surface top.

Frame: Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile units use 75mm twin wheel locking casters that attach via threaded inserts on underside of the steel frame assembly. Freestanding steel support legs and Mobile casters use the same threaded inserts and are interchangeable. Legs are available upon request.

Features of various cabinet configurations includes:

- Concealed door hinges and a variety of pulls available
- Full extension drawers



Rubix60W_cs_2008011

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

