# **Tables**







# SST TABLES

- Work surface is high-pressure laminate with PVC edgeband.
- Legs bolt to the 1"x 2" steel apron frame, which is a single welded assembly.
- Legs are fitted with adjustable leveling glides; casters are optional.
- Optional steel modesty panel available.
- · Wire management grommets available, optionally.

# **SST ROUND STANDARD SIZES**

MODEL	DIAMETER"	HEIGHT"
SST0042	42	29
SST0048	48	29
SST0060	60	29

#### **SST SQUARE STANDARD SIZES**

MODEL	DEPTH"	WIDTH"	HEIGHT"
SST4242	42	42	29
SST4848	48	48	29
SST6060	60	60	29

# SST RECTANGULAR STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
SST2436	24	36	29
SST2442	24	42	29
SST2448	24	48	29
SST2460	24	60	29
SST2472	24	72	29
SST2484	24	84	29
SST2496	24	96	29
SST3036	30	36	29
SST3042	30	42	29
SST3048	30	48	29
SST3060	30	60	29
SST3072	30	72	29
SST3084	30	84	29
SST3096	30	96	29
SST3660	36	60	29
SST3672	36	72	29
SST3684	36	84	29
SST3696	36	96	29




# To Order, Choose Finish Selections & Options


Work Surface: Choose from our selection of high-pressure laminates.

Edges: Choose a PVC edgeband.

Frame: Choose from our selection of powder coats for steel frame.

See **mediatechnologies**' Finish and Color Guide for options at www.mediatechnologies.com.











#### MODESTY PANELS



Shown with optional steel modesty panel

# General Specifications

**Table Top:** Table tops are 1-1/8" thick particle board core with .050" high-pressure laminate top surface and .030" phenolic backer. Edges are available in 3MM PVC (C). Corners on rectilinear and square tops are square with a 1/8" radius.

Base Assembly: The base consists of a 1" x 2" one piece, welded, tubular steel frame and four 1-1/2" square tubular steel legs. Legs are assembled to the frame by inserting a cross dowel into the top of each leg and bolting the legs to each corner of the frame assembly. The frame is then fastened to the table top brackets and screws. The bottom of each leg is fitted with an adjustable leveling glide or optionally with a 50MM black, twin wheel, locking caster.

Wire Management: Tables may be specified to include one or more 80MM grommets, provided for egress to the underside of the table.

**Modesty Panel:** A 12" high metal modesty/wire management panel may be specified as an option. The panel is formed to create a trough, 2 holes are cut at the bottom for wire egress.

cs-sst-190311

