

Desks





INTERACT







INTERACT

- Perfect for a variety of uses, including: Security, Mobile Reception, Circulation, Ticket Counter.
- Interact mobile desks come standard with 60mm twin wheel locking casters.
- Available in premium wood veneer with 3mm wood edges or high-pressure laminate with 3mm PVC edges.
- Contact your sales representative about customizing with one-of-a-kind logos or graphic designs. Note: Logos and graphics are not included.

EDGE TYPES FOR TRANSACTION TOP



3mm PVC



3mm

Wood

INTERACT DESK STANDARD SIZES

MODEL	DEPTH"	WIDTH"	TRANS TOP HEIGHT"	WORK SURFACE"
_ID48-42	30	48	42	30
_ID72-42	30	72	42	30
ID- 102-42	30	102	42	30

WOOD (HPL) PEDESTAL FILE/FILE

MODEL	DEPTH"	WIDTH"	HEIGHT"
WMPS121220-W-LL	20.75	14.8125	27

WOOD (HPL) PEDESTAL BOX/BOX/FILE

MODEL	DEPTH"	WIDTH"	HEIGHT"
WMPS661220-W-LL	20.75	14.8125	27

WOOD (HPL) PEDESTAL CUSHION TOP

MODEL	DEPTH"	WIDTH"	HEIGHT"
WMPS361120-W-LL-	20.75	14.8125	23.25

WOOD (HPL) PEDESTAL HANGING BOX/FILE

MODEL	DEPTH"	WIDTH"	HEIGHT"
WHPS61218-W-LL	18	14.8125	20



To Order, Choose Finish Selections & Options

Work Surface: Choose from our selection of high pressure laminates.

End Panels: Choose from our high pressure laminate or wood veneer options.

Base Frame: Choose from our selection of powder coats.

Edges: Choose from our selection of wood or PVC edges, as applicable.

See **mediatechnologies'** finish choices at https://www.mediatechnologies.com/resources/finishes

CORNERS







60mm locking casters

ACCESSORIES



Pencil Drawer



General Specifications

Modular Steel Frame: Frame shall be a welded assembly of 1-1/4" square 14 gage steel tube, drilled and tapped to receive casters and bored for connecting hardware. Finish shall be powder coat, manufacturer's standard colors.

Casework Modules General: Cases shall be constructed of 3/4" engineered wood panels with select grade oak or maple veneer or high-pressure laminate faces. Worksurfaces shall be 1-1/4" thick panels with 1-1/8" particle board core, horizontal grade (.045") high-pressure laminate upper surface and .030 backer sheet. Worksurface height shall be 30". Cases with oak or maple panels shall have 3mm wood edges. Cases finished in high-pressure laminate shall have 3mm PVC banding. Modules shall be bored to connect together with male/female assembly bolts.

Outer Modules: Vertical side panels shall be 1-3/16" thick. Front panel shall terminate and extend above the worksurface and shall in turn be terminated by a transaction ledge. Transaction ledge shall be constructed in the same manner as the main worksurface and shall have a bowed patron side hardwood edge. It shall be supported by the side panel and a steel support bracket.

Central Module: Front panel shall extend to the worksurface. Unit shall house two banks of drawers, each bank consisting of a lower file drawer and two upper box drawers. Each drawer shall use full extension ball bearing drawer slides rated at 100 lb capacity per pair.

Casters: Casters shall be 60mm twin wheel swivel casters with brake, rated at 100# per caster. Assembled unit shall use a total of (8) casters.

cs-interact-220406



