



L2424T-18 24"D X 24"W X 18"H



LEXINGTON



LEXINGTON OCCASIONAL TABLES

- Table top available in all standard laminates and optional veneer.
- Metal-to-metal leg connections using threaded inserts and machine bolts through a metal plate.
- Solid hardwood arched aprons.
- · Legs receive a 1" radius scoop on the inside faces.
- 5/8" X 1-1/4" hardwood edge, with a 13" reverse bevel.

LEXINGTON OCCASIONAL RECTANGLE STANDARD SIZES

| MODEL | DEPTH" | WIDTH" | HEIGHT" |
|-----------|--------|--------|---------|
| L2448T-18 | 24 | 48 | 18 |
| L2448T-22 | 24 | 48 | 22 |

LEXINGTON OCCASIONAL ROUND STANDARD SIZES

| MODEL | DIAMETER" | HEIGHT" | |
|-----------|-----------|---------|--|
| L0030T-18 | 30 | 18 | |
| L0030T-22 | 30 | 22 | |

LEXINGTON OCCASIONAL SQUARE STANDARD SIZES

| 017111271112 | 0.220 | | |
|--------------|--------|--------|---------|
| MODEL | DEPTH" | WIDTH" | HEIGHT" |
| L2424T-18 | 24 | 24 | 18 |
| L2424T-22 | 24 | 24 | 22 |

To Order, Choose Finish Selections & Options

Table Top: Choose your high pressure laminate.

Edges: Choose from our selection of PVC or wood veneers.

Base: Choose from our selection of wood veneers.

See **mediatechnologies**' Finish and Color Guide for choices at www.mediatechnologies.com.

General Specifications

Table Top: Table tops are 1-1/4" thick, three-ply engineered wood construction, with .050" high-pressure laminate (HPL) surface and a phenolic backer. The standard edge is 5/8"x1-5/8" solid red oak with a 1/2" radius all around.

Apron: The apron is 1"x3-3/4" with a 1/8" radius on the exposed edges. Each apron is machined to a gentle arch, 2" deep at midspan. Aprons span the distance between the legs and are attached with #8 screws.

Legs: The legs are 2-1/4" solid glued up red oak with a 3/8" radius on all long edges. They are attached to the top by means of a 5"x5/16" steel plate. The leg and the plate are joined by (2) 5/16-18 machine bolts screwed into a 1/2" diameter barrel nut which is embedded in the leg. The steel plate is attached to the table top by (5) 5/16-18 machine bolts which screw into 5/16-18 metal insert embedded in the top. Each leg is equipped with a leveling guide.



cs-lexington-190220

892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 F: 231.861.6678 www.mediatechnologies.com sales@mediatechnologies.com

