

ROCKFORD

Tables



RF-C4565RL

45"D X 65"W X 22"-32"H

ROCKFORD

Rectangle



ROCKFORD RECTANGLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C2436	24	36	22-32
RF-C2442	24	42	22-32
RF-C2448	24	48	22-32
RF-C2460	24	60	22-32
RF-C2472	24	72	22-32
RF-C3036	30	36	22-32
RF-C3042	30	42	22-32
RF-C3048	30	48	22-32
RF-C3060	30	60	22-32
RF-C3072	30	72	22-32

Beanie



ROCKFORD BEANIE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3060BNR	30	60	22-32

Square



ROCKFORD SQUARE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C4242	42	42	22-32
RF-C4848	48	48	22-32
RF-C6060	60	60	22-32

Diamond



ROCKFORD DIAMOND STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3242DM	32	42	22-32
RF-C3746DM	37	46	22-32

Trapezoid



ROCKFORD TRAPEZOID STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C30TRP	30	30	22-32

Pickle



ROCKFORD PICKLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3660G	36	60	22-32

Sprocket



ROCKFORD SPROCKET STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C6060S	60	60	22-32

Flair



ROCKFORD FLAIR STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3060FLR	30	60	22-32

Wave



ROCKFORD WAVE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3060WR	32.5	59.5	22-32

Raetsel



ROCKFORD RAETSEL STANDARD SIZE

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C4565RL	45	65	22-32
RF-C4565RL-14	45	65	14

Round



ROCKFORD ROUND STANDARD SIZES

MODEL	DIAMETER"	HEIGHT"
RF-C0042	42	22-32
RF-C0048	48	22-32
RF-C0060	60	22-32

Squircle



ROCKFORD SQUIRCLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3636SQR	36	36	22-32
RF-C4242SQR	42	42	22-32
RF-C4848SQR	48	48	22-32
RF-C5454SQR	54	54	22-32
RF-C6060SQR	60	60	22-32

Pac Man



ROCKFORD PAC MAN STANDARD SIZES

MODEL	DIA	HEIGHT"
RF-C0042PAC	42	22-32
RF-C0048PAC	48	22-32

Secil



ROCKFORD SECIL STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3772SC	37	72	22-32

Crescent



ROCKFORD CRESCENT STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3672CR	36	72	22-32

ROCKFORD "D" STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C3672D	36	72	22-32
RF-C4872D	48	72	22-32
RF-C6072D	60	72	22-32

"D" Shape



Clover



ROCKFORD CLOVER STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RF-C4848CL	48	48	22-32
RF-C6060CL	60	60	22-32

Quarter Round



ROCKFORD QTR ROUND STANDARD SIZES

MODEL	DIAMETER	HEIGHT"
RF-C36QR	24/36	22-32

The addition of casters will change the adjustable height range to 24" to 34"

ROCKFORD



RF-C4565RL


ROCKFORD ADJUSTABLE HEIGHT TABLES

- A variety of shapes and sizes allow collaboration in an ever-changing environment.
- 1-1/4" thick top with high-pressure laminate work surface and PVC edgebanding.
- Rigid 14-gauge two-piece steel adjustable legs, 22" to 32" heights. (The addition of casters will change the adjustable height range to 24" to 34")
- Standard leg finishes are (Top/Bottom): Silver/Silver, Black/Black, Black/Silver. Different powder coat colors are available upon request (may incur an upcharge).

● EDGE TYPES



● CORNERS



● CASTERS



To Order, Choose Finish Selections & Options

Work Surface: Choose from our selection of high-pressure laminates.

Edge: Choose from our selection of PVC edges.

Note: Sprocket, Beanie and Flair-top tables receive 2" radius corners.

Base: Choose from our selection of powder coats; indicate uniform color or top/bottom colors.

See **mediatechnologies'** finish selections at <https://www.mediatechnologies.com/resources/finishes>

● ACCESSORIES



Surfboard
SFB-1824



General Specifications

Work Surface: Table tops are 1-1/4" thick, with a 1-1/8" thick, three-ply particleboard core with .050 high-pressure laminate top and a .030" or thicker phenolic backer. Edges are 3mm PVC.

Adjustable Leg: Each leg is composed of an outer steel tube and an inner steel tube that can slide within it. The outer steel tube has a welded mounting plate that is 1/8" thick steel, welded to outer leg at the top and a reinforcement gusset of 1/8" thick steel, welded to mounting plate and outer leg. Each leg is provided with a leveling glide at the bottom.

Outer Tube: 14 gauge steel, 1-1/2" outer diameter, approx. 1-1/4" inner diameter. Perforated near the bottom with pass-through holes for (2) adjustment screws.

Inner Tube: 14 gauge steel, 1-1/4" outer diameter. Perforated and tapped for adjustment screws on 1" center to center distance providing for an adjustment range of 8". Adjustment screws must thread into inner leg and not just contact it.

Gusset: 1/8" thick steel, welded to mounting plate and outer tube.

Mounting Plate: 1/8" thick steel, welded to outer tube and gusset. Each leg is mounted to the table with seven (7) 1" #12 wood screws. Insert & machine thread screw (metal-to-metal) available upon request.



cs-rockford-211230

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

PURE MICHIGAN®