

# RUBIX 36"W

---

## Storage



CCB3672-24-MB-T  
OS3636-24-MB-T



24"D x 36"W x 72"H  
24"D x 36"W x 36"H

# RUBIX 36"W



## 36" WIDE RUBIX STORAGE UNITS

- High pressure laminate worksurfaces.
- Powder coated steel frame.
- Open Storage cabinets come with adjustable shelves.
- Optional 3" legs available upon request.
- Mobile units come equipped with 75mm casters.
- Not all configurations are available in every dimension combination.
- Totes for OTROS models (F1TBA-75 and F2TBB-150) sold separately.

### RUBIX 36"W STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
<b>OPEN STORAGE (OS)</b>			
OS36_-18-MB-T	18	36	29, 36, 42, 54
OS36_-24-MB-T	24	36	29, 36, 42, 54, 72
<b>CUPBOARD STORAGE (CS)</b>			
CS36_-18-MB-TT	18	36	29, 36, 42, 54
CS36_-24-MB-TT	24	36	29, 36, 42, 54, 72
<b>OPEN CUBICLE STORAGE (OCB) ADJ. SHELVES</b>			
OCB4-36_-18-MB-T	18	36	29, 36, 42
OCB4-36_-24-MB-T	24	36	29, 36, 42, 72
<b>OPEN CUBICLE STORAGE (OCB) FIXED SHELVES</b>			
OCB12-36_-_-MB-T	18, 24	36	29, 36, 42
<b>OPEN TOTE RAIL STORAGE WITH OPEN STORAGE (OTROS)</b>			
OTROS36_-24-MB-T	24	36	29, 36, 42
<b>CUPBOARD CUBICLE STORAGE (CCB)</b>			
CCB36_-18-MB-TT	18	36	29, 36, 42
CCB36_-24-MB-TT	24	36	29, 36, 42, 72
<b>DRAWER STORAGE (DS)</b>			
DS36_-_-MB-TT	18, 24	36	36, 42
<b>CUPBOARD WITH LATERAL FILE STORAGE (CSFSL)</b>			
<b>CUPBOARD WITH TOTE RAIL STORAGE (CSTR)</b>			
CSTR3672-24-MB-TT	24	36	72
<b>WARDROBE STORAGE (WRS)</b>			
WRS3672-24-MB-TT	24	36	72

### To Order, Choose Finish Selections & Options

**Work Surface (if applicable):** Choose from our selection of high pressure laminates.

**Cabinet:** Select HPL, melamine or veneer finish.

**Edge:** Choose from our selection of PVC or wood edges.

**Steel Frame:** Choose from our selection of powder coats.

**Pull:** Choose from our selection of Pulls.

See mediatechnologies' Finish and Color Guide for choices at <https://www.mediatechnologies.com/resources/finishes>

#### PULLS



#### CORNERS



#### CASTERS



### General Specifications

**Cabinet:** Are constructed with 3/4" thick engineered wood sides panels, sub-tops, vertical dividers and shelves. Backs are constructed with 3/4" thick engineered wood. Cabinet finish material includes high-pressure laminate and melamine with PVC edges and wood veneer with wood edges. Worksurface tops receive a high-pressure laminate surface. Cabinets 72"H or taller do not receive a worksurface top.

**Frame:** Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile units use 75mm twin wheel locking casters that attach via threaded inserts on underside of the steel frame assembly. Freestanding steel support legs and Mobile casters use the same threaded inserts and are interchangeable. Legs are available upon request.

Features of various cabinet configurations includes:

- concealed door hinges and a variety of pulls available
- full-extension drawers
- tote rails that are Stop-n-Tilt and fully fully extractable. Tote rails are mounted on 4-1/4" centers for use of both F1TBA and F2TBB totes (sold separately).



Rubix36\_CS\_200306

892 Industrial Park Drive  
Shelby, MI 49455  
P: 231.861.2194  
F: 231.861.6678  
[www.mediatechnologies.com](http://www.mediatechnologies.com)  
[sales@mediatechnologies.com](mailto:sales@mediatechnologies.com)

PURE MICHIGAN®