ENGAGE

Chairs & Stools



ENA-2529-4D

29”D X 25”W X 33.25”H, SEAT HEIGHT 18”

media technologies

ENGAGE



ENR-2829



EN-3029



ENA-2529



ENATR-2529



ENR-5129



EN-5329



ENA-4829



ENAW-3035

ENGAGE

- Engineered solid alder hardwood frames.
- High-resilience long lasting polyfoam.
- Arms or armless chair or loveseat.
- *Several models available to create a multitude of configurations.
- Powder coated steel legs, wood or caster available.
- Steel legs are equipped with leveling glides.

To Order, Choose Finish Selections & Options

Seat Cushions: Select fabric grade and pattern.

Legs: Choose from our powder coat options, or veneer finish for wood legs. Casters are black.

Table Surface: High Pressure Laminate selection (if applicable).

See **mediatechnologies'** Finish and Color Guide for choices. View our fabric choices at mediatechnologies.com.

ENGAGE SEAT STANDARD SIZES

MODEL	ARMS	DEPTH"	WIDTH"	SEAT HEIGHT"
		OVERALL HEIGHT 33.25"		
EN-3029	R & L	29	30	18
ENL-2829	LEFT	29	28	18
ENR-2829	RIGHT	29	28	18
ENA-2529	NONE	29	25	18
ENATR-2529	TABLET ARM R	29	25	18
ENAW-3035	NONE	35	30	18

ENGAGE DOUBLE SEAT STANDARD SIZES

MODEL	ARMS	DEPTH"	WIDTH"	SEAT HEIGHT"
		OVERALL HEIGHT 33.25"		
EN-5329	R & L	29	53	18
ENL-5129	LEFT	29	51	18
ENR-5129	RIGHT	29	51	18
ENA-4829	NONE	29	48	18

General Specifications

Seat: Engage seat is constructed with 4/4 Alder hardwood and is glued and stapled. 4/4 hardwood corner blocks are glued and stapled to the inner seat frame. The seat is then covered with 5" of foam with 1.8 density and a 36 ILD rating.

Back: The back is constructed with 4/4 Alder hardwood and is glued and stapled. 4/4 hardwood corner blocks are glued and stapled to the inner back frame. The back is then covered with 2.5" of foam with 1.8 density and a 24 ILD rating. The back is secured to the seat with T-nuts and 4 bolts.

Arms: are constructed with 4/4, 5/4 and 6/4 Alder hardwood and is glued and stapled. 4/4 hardwood corner blocks are glued and stapled to the inner frame. The arms are then prepared with emelin and covered with 1/2" of foam. Arms are attached to the seat and back frame with T-nuts and 3 bolts. Note: Arms are identified as "right" or "left" from the perspective of one who is seated in the seat.

Tablet Arm: Tablet arm work surface is 3/4" thick. Top of work surface is .050 high-pressure laminate with .030 phenolic backer. Work surface is mounted to a powder coated steel tube which is fixed to the seat frame. Edgebanding is 3mm PVC.

ENGAGE OPTIONS






FULL TIME LEGS & CASTERS



Standard steel leg



Wood post leg



75mm caster



Lift handle

LEG & CASTER DESCRIPTIONS

- Metal legs are fabricated of 5/16" plate steel and include a square mounting plate and a pair of decorative gussets. The bottom of each leg is fitted with a threaded weld nut and 1-7/8" ABS black leveling glide.
- Softec, twin-wheel non-locking 75mm black casters.
- Wood post 3-1/2" x 3-1/2" with a 45° chamfer bottom edge. Posts are attached via 5/16"-18 bolt, washer and propeller nut.

MODEL NUMBER SUFFIXES FOR LEGS & CASTERS
(models with casters receive lift handle)

-2D - 2 metal legs and 2 casters
-4D - 4 metal legs
-2W - 2 wood legs and 2 casters
-4W - 4 wood legs
-4C - 4 casters

MODEL NUMBER SUFFIXES FOR POWER/CONNECTIVITY
(after legs) (no designation) - no power/connectivity panel
-EL - Power/connectivity panel on left side
-ER - power/connectivity panel on right side

CONNECTIVITY



DUET power unit
ADUF-1P2U-72-W

DUET

- For use in upholstered furniture
- 1 Power / 1 Dual USB
- 2 amps each USB charging port
- UL Listed
- Face mount shown
- White, silver and black face plate available
- 72" and 120" cords available

! Connectivity panels can only be mounted on the side surfaces of Engage seating.

media technologies™

892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194
F: 231.861.6678
www.mediatechnologies.com
sales@mediatechnologies.com

PURE MICHIGAN®