

# FULL TIME OTTABLES

---

## Occasional Tables



FTDT-36-5C

36" DIA X 18"H

# FULL TIME OTTABLES



FTRT-2436  
Rectangle



FTDT-36  
Round



FTST-3636  
Square

## FULL TIME OTTABLES

- Upholstered 1" thick assembled wood frame is topped with a 1" thick high pressure laminate work surface.
- Work surface is 18" high with 3mm PVC edges.
- Equipped with steel Duo legs with leveling glides.
- Casters are optional.
- Mates well with Full Time Ottomans!

### ROUND STANDARD SIZES

MODEL	DIA.	HEIGHT"
FTDT-20	20	18
FTDT-36	36	18
FTDT-51	51	18

### CURVE STANDARD SIZES

MODEL	CURVE	RETURNS	HEIGHT
FTCT-60	60°	24	18

### SQUARE STANDARD SIZES

MODEL	WIDTH"	HEIGHT"
FTST-2424	24	18
FTST-3636	36	18

### RECTANGLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
FTRT-1836	18	36	18
FTRT-2436	24	36	18
FTRT-2448	24	48	18

## To Order, Choose Finish Selections & Options

**Upholstery:** Choose upholstery.

**Work surface:** Choose a high pressure laminate.

**Edges:** Choose from our selection of PVC edges.

**Steel Legs:** Choose from our selection of powder coats.

See **mediatechnologies'** finish selections at <https://www.mediatechnologies.com/resources/finishes>  
View our fabric choices at <https://www.mediatechnologies.com/resources/fabrics>

### EDGE TYPES



C  
3mm  
PVC

### CASTERS



Locking  
Casters

### CONNECTIVITY

See our Connect Brochure.

Connectivity available in workurface only.

### General Specifications

**Work surface:** Work surfaces are 1" thick, with a 7/8" particleboard core, .050" high-pressure laminate top and a .030 or thicker phenolic backer. Edge is 1/8" PVC. Work surface shapes match the base shapes and are available in round, square, rectangle and 30°curve shapes.

**Base:** Upholstered base fabricated in round, square, rectangle and 60°curve shapes. Interior construction consists of a structural wood frame wrapped with 1/2" thick, 2.3# density foam on the sides with a Dacron slip cover.

**Leg Assemblies:** Each leg is a weldment fabricated from 5/16" plate steel with a square mounting plate and curved vertical member. The bottom of each leg is fitted with a threaded weld nut and 1-7/8" black leveling glide. Powder coat finish. Four 75mm diameter casters can be substituted for legs at no charge. (FTD-20 uses (5) 50mm diameter casters.)



892 Industrial Park Drive  
Shelby, MI 49455  
P: 231.861.2194  
F: 231.861.6678  
[www.mediatechnologies.com](http://www.mediatechnologies.com)  
[sales@mediatechnologies.com](mailto:sales@mediatechnologies.com)

cs-fulltime\_ottables-211020

PURE MICHIGAN®