

## Storage



18"D x 48"W x 54"H



W4854-18-MB-T

# RUBIX 48"W



Open Storage (OS) OS4836-24-MB-T



48" WIDE RUBIX STORAGE UNITS
High pressure laminate worksurfaces.

and oak or maple veneer.

Powder coated steel frame.

Cupboard Storage (CS) CS4836-24-MB-TT

• Cabinet material options include melamine, high pressure laminate

• Available in a variety of heights including: 29"H, 36"H, 42"H, 54"H.

• Not all configurations are available in every dimension combination.

Totes for OTROS models (F1TBA-75 and F2TBB-150) sold separately.

• Open Storage cabinets come with adjustable shelves.

• Mobile units come equipped with 75mm casters.

• Optional 3" legs available upon request.



Open Cubicle Storage (OCB) Adjustable Shelves OCB9-4836-24-MB-T



Cupboard Cubicle Storage (CCB) CCB-4836-24-MB-TT



Open Cubicle Storage (OCB) Fixed Shelves OCB204842-18-MB-T



Open Tote Rail Storage (OTR) OTROS-4829-24-MB-T

### To Order, Choose Finish Selections & Options

Work Surface (if applicable): Choose from our selection of high pressure laminates.


Cabinet: Select HPL, melamine or veneer finish.

Edge: Choose from our selection of PVC or wood edges.

Steel Frame: Choose from our selection of powder coats.

Pull: Choose from our selection of Pulls.

See mediatechnologies' Finish and Color Guide for choices at https://www.mediatechnologies.com/resources/finishes



#### General Specifications

Cabinet: Are constructed with 3/4" thick engineered wood sides panels, sub-tops, vertical dividers and shelves. Backs are constructed with 3/4" thick engineered wood. Cabinet finish material includes high-pressure laminate and melamine with PVC edges and wood veneer with wood edges. Worksurface tops receive a high-pressure laminate surface. Cabinets 72"H or taller do not receive a worksurface top.

Frame: Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile units use 75mm twin wheel locking casters that attach via threaded inserts on underside of the steel frame assembly. Freestanding steel support legs and Mobile casters use the same threaded inserts and are interchangeable. Legs are available upon request.

Features of various cabinet configurations includes:

 Concealed door hinges and a variety of pulls available
 Tote rails that are Stop-n-Tilt and fully fully extractable. Tote rails are mounted on 4-1/4" centers for use of both F1TBA and F2TBB totes (sold separately).

Rubix48W\_cs\_200306



#### **RUBIX 48"W STANDARD SIZES**

MODEL	DEPTH"	WIDTH"	HEIGHT"
		OPEN STORAGE (OS)	
OS48MB-T	18, 24	48	29, 36, 42, 54
OPEN CUBICLE STORAGE (OCB) ADJ. SHELVES			
OCB12-48MB-T	18, 24	48	29, 36, 42, 54
OCB9-4836MB-T	18, 24	48	29, 36, 42, 54
	STORAGE FIXED COMPARTMENTS (OCB)		
OCB20-4842MB-T	18, 24	48	42
	<b>OPEN TOTE RAIL STORAGE (OTR)</b>		
OTROS4824-MB-T	24	48	29, 36, 42
	CUPBOARD STORAGE (CS)		
CS48MB-T	18, 24	48	29, 36, 42, 54
	CUPBOARD CUBICLE STORAGE (CCB)		
CCB48MB-T	18, 24	48	29, 36, 42
	WARDROBE STORAGE (W)		
W4854MB-T	18, 24	48	54



892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 F: 231.861.6678 www.mediatechnologies.com sales@mediatechnologies.com